

Product Information

TEGO® Antifoam MR 465

PRODUCT DESCRIPTION

TEGO® Antifoam MR 465 is an antifoam based on organo-modified siloxanes for foam control in non-aqueous media.

Typical Properties

Property	Unit	Value
Appearance		Yellowish to brownish liquid
Density at 25°C	g/cm ³	1.00
Viscosity at 25°C	mPa·s	800

The data represents typical values (no product specification)

TYPICAL APPLICATIONS

TEGO® Antifoam MR 465 is used as an antifoam component in the production of additive packages for diesel fuel.

Furthermore, TEGO® Antifoam MR 465 may be used for foam control in various other non-aqueous applications, e.g. lubricants.

Product Composition

Product Composition	Unit	Value
Active Content	wt%	78-82
Silicon (Si) Content	%	≤9

The data represents typical values (no product specification)

BENEFITS & ADVANTAGES

Resulting from its special modification TEGO® Antifoam MR 465 outperforms conventional products for the formulation of diesel additive packages in many respects.

Efficiency in dry and wet fuel

TEGO® Antifoam MR 465 reduces substantially and reliably both, foam collapse time and initial foam height.

TEGO® Antifoam MR 465 maintains its outstanding per-

formance even in wet fuel and after a storage time of the treated fuel exceeding 4 weeks.

Water shedding properties



Excellent water shedding properties could be achieved by using a sulphur free demulsifier.

Reduced treat rate

Compared to conventional antifoams based on polyether siloxanes, TEGO® Antifoam MR 465 proved to be much more efficient resulting in strongly reduced treat rates.

Compatibility with additive packages

TEGO® Antifoam MR 465 may be incorporated into diesel additive packages requiring only small amounts or even no additional use of solvents, i. e. TEGO® Antifoam MR 465 supports the formulation of low-solvent additive packages. It shows excellent compatibility with a wide range of packages, regardless the solvent base, detergents, etc. TEGO® Antifoam MR 465 can be incorporated in most additive packages yielding clear and stable formulations even at temperatures as low as -20°C



DOSAGE

Depending on the composition of the additive package and the fuel grade the dosage of TEGO® Antifoam MR 465 may vary over a wide range. Consequently, the optimum dosage has to be evaluated in suitable test series. For first trials we recommend a dosage of 6 to 8 ppm referred to the treated fuel.

HANDLING & PROCESSING

TEGO® Antifoam MR 465 is soluble in a variety of aromatic and aliphatic solvents (e. g. long chain alcohols). This provides maximum flexibility in the formulation of diesel additive packages. Examples of suitable solvents for TEGO® Antifoam MR 507 include

- Aromatic naphtha
- Toluene
- Isodecanol
- 2-ethylhexanol
- Hexanol
- Ethanol

PACKAGING

Pallet size: 4 x 200 kg = 800 kg

12 x 25 kg = 300 kg

1 000 kg containers

Batch size approx. 4 000 kg

STORAGE

In original closed containers TEGO® Antifoam MR 465 can be stored at room temperatures for at least 1 year.

HAZARDOUS SUBSTANCE

Information concerning

- Classification and labelling according to regulations for transport and for dangerous substances
- Protective measures for storage and handling
- Measures in case of accidents and fire
- Toxicity and ecological effects

is given in our material safety data sheets.

REGISTRATION LISTING SUMMARY

The relevant components of TEGO® Antifoam MR 465 are listed/registered or exempt in the following chemical inventories:

Registration Listings

Registry	Status
Australia (AIIC)	Yes
Canada (DSL)	Yes
EU (EINECS/ELINCS)	Yes
South Korea (KECL)	Yes
Taiwan (TCSI)	Yes
USA (TSCA)	Yes

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH

Interface & Performance
Goldschmidtstraße 100
45127 Essen, Germany
Phone Europe +49 201 173-2665
Phone Asia +86 21 61191 125
Phone Americas +1 804 727 0700
interface-performance@evonik.com
[evonik.click/interface-performance](#)